

20.000 - 70.000 l/h Discs, cartridges, bags

Typical applications






Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Choice of DOE cartridges, thin discs (for largest filter area), thick discs (for highest dirt holding capacity) or bags
- Discs can be removed in manageable stacks
- All PP construction, max. temperature PP 80°C
- Wheels for portability may be removed once installed
- Multifunctional large round slurry tank with sloping bottom
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection, dry run protection, contact manometer



Filter Systems series 36

www.hendor.com

Pump	l/h	kW	Union (d/DN)		Hose		Type	Chamber	Medium	Slurrytank	Material
			In	Out	In	Out					
Magnetic drive	26000	3					M300	K P Ph B	S	PP-EPDM	
	52000	2x3				2-M300					
	35000	4	63/50	63/50	2 1/2"	2 1/2"	M400				
	70000	2x4				2-M400					
Mechanical seal	24000	2,2					S220	(2-) 362A	S	PP-EPDM	
	48000	2x2,2				2-S220					
	32000	3	63/50	63/50	2 1/2"	2 1/2"	S300				
	64000	2x3				2-S300					
Selection:						M400	362A	P	S	PP	

K = cartridges

Qty x L
362A-K = 36 x 20"

P = discs

Qty OD/ID m²
362A-P = 61 x 460/100 9
362A-Ph = 33 x 460/100 5

B = bags

Qty L/OD
362Z-B = 7 x 500/130